

| | |
|---|---|
| Codice articolo Product code: | 2007003 |
| Descrizione Description: | BUSSOLA ST-ST PER FIBRA MONOMODALE ST-ST ADAPTER FOR SINGLE-MODE FIBER |



Descrizione

Bussola ST-ST Simplex per l'accoppiamento, all'interno di cassette o box ottici, di connettori fibra monomodali.

Caratteristiche principali

| | |
|-------------------------|---|
| Materiali | Corpo in lega di zinco nichelato, cappuccio antipolvere in materiale plastico, sleeve in bronzo fosforoso |
| Perdita inserzione | Tipica 0,15 dB |
| Tipo fibra | Monomodale |
| Colore | Corpo grigio metall. Cappuccio rosso |
| Installazione | Su cassette o box ottici |
| Temperatura d'esercizio | Da -20° C a +60° C |

Prestazioni

| | |
|----------|--|
| Standard | ANSI/TIA 568-C.3 IEC 61754 IEC 60874 |
|----------|--|

Confezionamento

| | |
|-------------------------|--|
| Confezione | Sacchetto in plastica 80x50 mm – 1 pz |
| Ogni confezione include | - 1 bussola ST-ST SM - 2 cappucci antipolvere |

Description

Simplex ST-ST adapter for joining single-mode connectors inside fiber optic patch panels or enclosures.

General features

| | |
|-----------------------|---|
| Materials | Nickel plated zinc alloy body, plastic dust cap, phosphor bronze sleeve |
| Insertion Loss | Typical 0,15 dB |
| Fiber type | Single-mode |
| Color | Body metal gray Dust cap red |
| Installation | On fiber optic patch panel or fiber optic enclosure |
| Operating temperature | From -20° C to +60° C |

Performance

| | |
|-----------|--|
| Approvals | ANSI/TIA 568-C.3 IEC 61754 IEC 60874 |
|-----------|--|

Packaging

| | |
|-----------------------|---------------------------------------|
| Package | Plastic bag 80x50 mm – 1 pz |
| Each package includes | - 1 SM ST-ST adapter - 2 dust caps |

| | |
|----------------------------------|---|
| Codice articolo Product code: | 2007003 |
| Descrizione Description: | BUSSOLA ST-ST PER FIBRA MONOMODALE ST-ST ADAPTER FOR SINGLE-MODE FIBER |

DISEGNO TECNICO / TECHNICAL DRAWINGS

