

technical data sheet

Description :

WALL MOUNTED IP55 CABINETS Front blind door

Wall mounted IP55 cabinets are designed for the containment of the main equipment for structured cabling and LAN networks in environments where it is required a high protection degree. The solution with a new design allows the integration of a wide range of accessories needed in the most advanced hi-tech environments. Racks have an IP55 protection degree and are available with a depth of 450 or 600 mm, equipped with front blind door and hinged roof.

CODE	DESCRIPTION	DIMENSIONS (mm)			LOADING WEIGHT
		W	D	Н	KG
2010302	Cabinet IP55 19" 600x450x9U blind door	600	450	543	80
2010322	Cabinet IP55 19" 600x600x9U blind door	600	600	543	80
2010303	Cabinet IP55 19" 600x450x12U blind door	600	450	676	100
2010323	Cabinet IP55 19" 600x600x12U blind door	600	600	676	100
2010304	Cabinet IP55 19" 600x450x16U blind door	600	450	854	120
2010324	Cabinet IP55 19" 600x600x16U blind door	600	600	854	120



GENERAL CHARACTERISTICS

- Steel sheet structure
- Colour: Grey RAL 7035
- Front blind door
- Locking system with double key locks
- No. 2 19" numbered front uprights adjustable in depth; no. 4 19" numbered front and rear uprights for racks with depth of 600 mm
- Cable inlets on the base with PG cable glands and plastic gaskets pre-installed
- Hinged roof with ventilation slots
- Roof is designed to house forced ventilation unit with 2 fans
- Air filters on the sides with external covers
- Degree of protection IP55 compliant to EN 60529
- Degree of impact resistance: IK10
- Equipped for grounding
- Loading weight: from 80 to 120 Kg depending on the model

QUBIX S.p.A. Networking solutions – Via Canada, 22/A – 35127 Padova – Italy Tel. +39 049 7801994 – Fax +39 049 775667 – <u>http://www.qubix.it</u>

Rev. 01-23

Qubix S.p.A. si riserva di apportare modifiche e migliorie in qualsiasi momento senza preavviso Qubix S.p.A. reserves the right to make changes and improvements at any time without notice



