

Network Video Recorder 32 channels

2045354 – QPNVR3204



Key features

32 Channels

Third-party IP cameras supported with ONVIF conformance: Profile S, Profile G, Profile T

Supports 2-ch HDMI, 1-ch VGA, HDMI2 at up to 4K (3840x2160)

Up to 12MP resolution recording

Compression H.264/ H.265 and Ultra H.265

Accurate retrieval, instant playback

4 SATA interfaces HDD up to 8 TB each

Support various VCA detection alarm and VCA search

Dewarping support for fisheye cameras

Support for P2P, UPnP, NTP, DHCP, PPPoE

Support for client mobile access



Specifications

Artile nr	2045354 – QPNVR3204
Channels	32
Two-way audio Input	1-ch, RCA
Network	
Incoming bandwidth	320 Mbps
Outgoing bandwidth	320 Mbps
Users	Up to 128
Video/Audio output	
HDMI/VGA output	HDMI1: 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz HDMI2: 4K (3840x2160) /60Hz, 4K (3840x2160) /30Hz, 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz VGA: 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz
Recording resolution	12M/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Audio output	1-ch, RCA
Synchronous playback	Up to 16 channels
Decoding	
Decoding format	Ultra 265, H.265, H.264, MJPEG
Live View/Playback	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	3 x 12MP@25, 4 x 4K@30, 8 x 4MP@30, 16 x 1080p@30, 32 x 960p@25
Smart functions	
Detection	Face detection, intrusion detection, line crossing, audio, defocus, scene change, auto tracking
Search	Face search
Statistics	People counting
Hard Disk	
SATA	4 SATA interfaces
Capacity	Up to 8 TB for each HDD
Interfaces	
Network interface	2 RJ-45 10M/100M/1000M self-adaptive Ethernet interfaces
USB interface	2 x USB 2.0 and 1 x USB 3.0
Serial interface	1 x RS485
Alarm I/O	16/4
General	
Power supply	12V DC
Power consumption	≤ 12 W (without HDD)
Working Environment	-10°C ~ + 55°C
Dimensions	44 x 440 x 344 mm
Weight	3,14 kg (without HDD)

Rear view



Dimensions

