

Mini 4S+ PREMIUM PACKAGE

- 1

MINI 4S+ Splicer
- 2

Cleaver Softcase
- 3

MINI 50G+ Cleaver
- 4

Power Cord
- 5

USB Cable
- 6

AC Adapter
- 7

Car Cigar Cable
- 8

Cooling Tray

9

Spare Electrode

10

SOC Heater Block

11

SOC Holder

12

2 Battery Packs

13

Shoulder Strap

14

User Manual CD

15

Hand Carrying Case

SPECIFICATIONS

Splicing Method	Active Alignment DAA(Digitalized Active Alignment)	Illumination	LED emitting white light (1 piece)
Average Loss	SM(0.02dB) / MM(0.01dB) / DS(0.04dB) / NZDS(0.04dB) / G.657(0.02dB)	Battery	Typical 200 Cycles (Splice & Heat) / single battery <2 Batteries Standard>
Return Loss	>>60dB	Power Supply	AC 100-240V input or DC 9~14V
Splice Time	10s average SM / SM 7s Quick mode	Monitor	Color 4.3" LCD monitor, with Touch Screen (Tempered Glass)
Electrodve Lifespan	>5,500 arcs	Cameras	2 CCD camera system
Applicable Fiber	SM(ITU-T G.652&G.657), MM(ITU-T G.651), DS(ITU-T G.653), NZDS(ITU-T G.655), IT-G657A, IT-G657B / 0.25mm, 0.9mm, 2.0mm, 2.4mm, 3.0mm, FLAT(indoor cable)	Magnification	XY style : 150 power, X/Y : 300 power
Cleaved Length	Coating Diameter < 0.25mm = 8-16mm, Coating Diameter > 0.25mm = 16mm minimum	Fiber Display	X/Y or XY, single X.Y
Coating Diameter	100-1,000um	Weight	1.39Kg (without battery)
Cladding Diameter	80-150um	Size	122mm X 124mm X 138 mm
Heating Programs	Factory installed mode : 11, User installable mode : 23	Wind Protection	The max wind speed 15m/s
Heating Time	Typical 15s	Operating Environment	Elevation 0-5,000 meters, -20~60°C, 0~95% relative humidity
Protection Sleeve	40mm, 60mm, SOC Connector	Storage Condition	122mm X 124mm X 138 mm
Data Output	Micro HDMI-USB master device	Pull Test	1.96~2.25N (standard)
Splice Programs	Factory installed mode: 33, User installable mode: 70+	Attenuation splicing	Range : 0.1dB ~ 20dB (0.1dB step)
Splice Memory	Up to 5,000 records and 2,000 splice images		



(Kwang Yi Building) 80, Dongseo-daero 179beon-gil, Yuseong-gu, Daejeon 305-320, Korea
Tel +82-42-716-7221 / Fax +82-42-716-7223 / E-mail sales@fiberfox.co.kr

www.fiberfox.co.kr

Mini 4S+

A Frontier Never Follows

Fiberfox is the first manufacturer of an Active Alignment Splicer

1.39

kg

400

cycles

7

sec

0.02

dB



www.fiberfox.co.kr





Mini 4S+ CHARACTERISTIC

1 Heating Time
15sec with 60mm sleeve




2 The Fast Splicing Time
7sec with SM fiber

3 400 cycles (splicing & heating)
with Two Batteries

4 Universal Holder
250 μ m / 900 μ m / 2~3 Φ / Indoor

5 LED Injection System (No Mirrors)

6 SOC Compatible



Elevation
0~5000meter

The max wind
speed 15m/s

Temperature
-15~60 $^{\circ}$ C

relative humidity
0~95%

