

Codice articolo Product code:	2007023FAPC
Descrizione Description:	BUSSOLA FLANGELESS LC/APC- LC/APC DUPLEX PER FIBRA MONOMODALE FLANGELESS DUPLEX LC/APC-LC/APC ADAPTER FOR SINGLE-MODE FIBER



Descrizione

Bussola LC-LC Duplex tipo APC senza flange per l'accoppiamento, all'interno di cassette o box ottici, di connettori fibra monomodali di tipo LC APC.

Caratteristiche principali

Materiali	Corpo in polimero PBT UL 94V-0, cappuccio antipolvere in materiale plastico, sleeve in zirconia ceramica
Connessione	LC/LC Duplex tipo APC
Perdita inserzione	Tipica 0,2 dB
Tipo fibra	Monomodale
Colore	Corpo: verde Cappucci: bianchi
Installazione	Su cassette o box ottici
Temperatura d'esercizio	Da -20° C a +60° C

Prestazioni

Standard	ISO/IEC 11801 ANSI/TIA 568.3-D IEC 61754 IEC 60874
----------	---

Confezionamento

Confezione	Box in cartone
Ogni confezione include	- 48 bussole LC-LC Duplex APC SM flangeless con cappucci antipolvere

Description

Flangeless APC type Duplex LC-LC adapter for joining APC LC single-mode connectors inside fiber optic patch panels or enclosures.

General features

Materials	Body in UL 94V-0 PBT polymer, dust caps in plastic material, sleeve in zirconia ceramic
Connection	Duplex LC-LC, APC type
Insertion Loss	Typical 0,2 dB
Fiber type	Single-mode
Color	Body: green Dust caps: white
Installation	On fiber optic patch panel or fiber optic enclosure
Operating temperature	From -20° C to +60° C

Performance

Approvals	ISO/IEC 11801 ANSI/TIA 568.3-D IEC 61754 IEC 60874
-----------	---

Packaging

Package	Cartoon box
Each package includes	- 48 flangeless SM APC Duplex LC-LC adapters with dust caps

Codice articolo Product code:	2007023FAPC
Descrizione Description:	BUSSOLA FLANGELESS LC/APC- LC/APC DUPLEX PER FIBRA MONOMODALE FLANGELESS DUPLEX LC/APC-LC/APC ADAPTER FOR SINGLE-MODE FIBER

DISEGNO TECNICO / TECHNICAL DRAWINGS

